## Technical Specification | Mini Pumps

# **Maxi Lime**

Part No: Various







Height: 115mm Width: 99mm Depth: 44mm Weight: 0.47kg

### **Power Supply:**

- 230V AC, 15W
- 1PH 50 Hz
- 3A volt-free alarm wires, N.O., N.C. contacts rated @ 5A inductive at 230V

#### In The Box:

- Maxi Lime pump
- Breather tube
- Discharge tube with connector and length of insulation
- Internal conduit sleeve
- Conduit front and back
- Elbow kit
- Trunking
- Ceiling plate
- Inlet hose, rawl plugs and screws
- Cable ties

#### **Other Features:**

- Hall effect semi conductor level sensors, with high level safety
- Fully potted
- Thermally protected
- CE marked

#### **Performance:**


- Water flow rate: 34ltrs/hour at zero head
- Maximum recommended head: 15 metres
- 35dB(A) @ 1 metre



VERTICAL PUMPING HEAD	HORIZONTAL			
	30m	60m	90m	100m Max
3m		20	19	
2m	22	22	21	
1m		24	21	Ltr/Hr

#### **Systems Available:**

BBJ	lvory	FP2213
Inoac	lvory	FP2214
Optimal	White	FP2290
Artiplastic	lvory	FP2405
OEM		FP2215





The Aspen Maxi Lime pump is completely unique, in both design and installation advantages. The pump is clipped directly onto the reservoir so there is minimal suction lift. By connecting the drain hose to the reservoir of the pump unit, condensate water can be pumped away to a suitable drain.

The pump fits securely into a specifically designed elbow that holds it horizontally to ensure reliable operation. The pump and elbow are reversible therefore it can be installed easily on either side of an evaporator unit. The Lime system makes installation easy by providing a pump complete with the conduit trunking, in which the pump and all pipework are hidden. This system allows easy access for maintenance and ensures that the reservoir is level at all times.

- Completely reversible
- Quick and easy to install



Apex Way Hailsham East Sussex BN27 3WA T: +44 (0)1323 848842 F: +44 (0)1323 848846 sales@aspenpumps.com

www.aspenpumps.com