


Fieldpiece

Voltage Accessory Head


Model: AVH1



OPERATOR'S MANUAL

Description

Converts volts to millivolts for use with data logger for direct display and recording of voltage through the meter's mV scale. Use it with the EHDL1 to record MIN and MAX.




EHDL1

DL2

Operation

1. Slide onto EHDL1 or DL2.
2. Attach test leads to AVH1.
3. Set the meter mV range to read volts directly.



Specifications

Conversion rate: 1mVAC/1VAC or 1mVDC/1VDC

Resolution: 0.1V for meters with 0.1mV

Accuracy: (at 73°F ± 10°F <95%RH)

DC: ±(0.5%rdg + 1 dgt)

AC: ±(1.0%rdg + 4 dgts)

Max voltage: 600V AC or DC

Input impedance: 1MΩ

Operating temp: 32°F to 120°F at <95%RH

Storage temp: -4°F to 140°F

Safety: CE- mark approved, EN61010-1 approval, Cat III 600V

Warranty

The product is warranted to the original purchaser against defects in material or workmanship for a period of one (1) year from the date of purchase. During the warranty period, Fieldpiece Instruments will, at its option, replace or repair the defective unit.

This warranty does not apply to defects resulting from abuse, neglect, accident, unauthorized repair, alteration, or unreasonable use of the instrument. Any implied warranty arising out of the sale of Fieldpiece's products including but not limited to implied warranties of merchantability, and fitness for purpose, are limited to the above. Fieldpiece shall not be liable for incidental or consequential damages.

Service

Any defective AVH1 should be returned to Fieldpiece Instruments for warranty service along with proof of purchase.

Fieldpiece Instruments, Inc.
580 West Central Ave. Suite A
Brea, CA 92821


Phone: (714) 257-9060 Fax: (714) 257-9069

www.fieldpiece.com

Fieldpiece

Voltage Accessory Head


Model: AVH1



OPERATOR'S MANUAL

Description

Converts volts to millivolts for use with data logger for direct display and recording of voltage through the meter's mV scale. Use it with the EHDL1 to record MIN and MAX.




EHDL1

DL2

Operation

1. Slide onto EHDL1 or DL2.
2. Attach test leads to AVH1.
3. Set the meter mV range to read volts directly.



Specifications

Conversion rate: 1mVAC/1VAC or 1mVDC/1VDC

Resolution: 0.1V for meters with 0.1mV

Accuracy: (at 73°F ± 10°F <95%RH)

DC: ±(0.5%rdg + 1 dgt)

AC: ±(1.0%rdg + 4 dgts)

Max voltage: 600V AC or DC

Input impedance: 1MΩ

Operating temp: 32°F to 120°F at <95%RH

Storage temp: -4°F to 140°F

Safety: CE- mark approved, EN61010-1 approval, Cat III 600V

Warranty

The product is warranted to the original purchaser against defects in material or workmanship for a period of one (1) year from the date of purchase. During the warranty period, Fieldpiece Instruments will, at its option, replace or repair the defective unit.

This warranty does not apply to defects resulting from abuse, neglect, accident, unauthorized repair, alteration, or unreasonable use of the instrument. Any implied warranty arising out of the sale of Fieldpiece's products including but not limited to implied warranties of merchantability, and fitness for purpose, are limited to the above. Fieldpiece shall not be liable for incidental or consequential damages.

Fieldpiece Instruments, Inc.
580 West Central Ave. Suite A
Brea, CA 92821

Phone: (714) 257-9060 Fax: (714) 257-9069

www.fieldpiece.com