



A/C Maintenance Equipment

STINGER




Stinger™

A/C REFRIGERANT RECOVERY UNIT

The Stinger™ is one of the highest quality refrigerant recovery units on the market. Its powerful compressor will pump refrigerants at a quick pace while preventing pollutants from escaping into the environment.

Features

- NEW** Vacuum Shut Off Allowing for Unattended Recovery Operation
- NEW** Easy-to-Read, Low Vacuum/Tank Full LED
- NEW** Carrying Strap
- NEW** Improved Packaging to Protect Knobs and Gauges
 - Handles Almost All Refrigerants
 - Labeling on Rear of Unit with Directions for Proper Connection
 - Capable of Pumping Virgin Refrigerant Without Damaging the Compressor
 - Lightweight and Compact
 - One Year Over-the-Counter Warranty





"The Stinger has earned the trusted ARI Performance Certified™ seal, an assurance of the product's performance in accordance with ARI Standard 740."

The new Stinger™ comes equipped with the new vacuum shut off allowing for unattended recovery operation, an easy-to-read low vacuum/tank full LED, carrying strap, and improved packaging to protect knobs and gauges. Providing you with new safety and reliability, the upgraded Stinger™ is capable of recovering all commonly used* CFC, HFC and HCFC refrigerants, including R-410A (Puron™). The unit is easy to operate and is ideal for evacuating both residential and light commercial systems. A simple purge system prevents cross contamination of refrigerants without changing hose.

*Not for use with R-11, R-113 or R-123


Specifications

Refrigerants	R-12, R-22, R-114, R134a, R-401A, R-401B, R-401C, R-402A, R-402B, R-404A, R-406A, R-407A, R-407B, R-407C, R-407D, R-408A, R-409A, R-410A, R-411A, R-411B, R-412A, R-500A, R-502B, R-507, R-509
Power Source (available)	110/120 VAC, 1 Phase, 50/60 Hz, 8 Amps 220 VAC, 1 Phase, 50/60 Hz, 4 Amps
Compressor Type	0.8 HP High Performance Oil-less
Vacuum Rating	15" Hg+
High Pressure Limit	550 PSI (37.9 bar)
R-22 Recovery Rates	Vapor Recovery Rate: 0.29lbs./min. (0.13kg/min.) Liquid Recovery Rate: 3.53lbs./min. (1.60 kg/min.) Liquid Push / Pull: 12.28lbs./min. (5.58 kg/min.)
Refrigerant 134a	Vapor Recovery Rate: 0.22lbs./min. (0.10 kg/min.) Liquid Recovery Rate: 2.66lbs./min. (1.21 kg/min.) Liquid Push / Pull: 10.96 lbs./min. (4.98 kg/min.)
Refrigerant 410a	Vapor Recovery Rate: 0.22lbs./min. (0.10 kg/min.) Liquid Recovery Rate: 3.00lbs./min. (1.37 kg/min.) Liquid Push / Pull: 14.58lbs./min. (6.63 kg/min.)
Auto 80% Tank Shut-Off	Optional
Weight	24 lbs. (11 kg)

Ordering Information

2006-3800	Domestic 120V
2006-3801	Domestic 120V w/80%
2006-3807	European 230V
2006-3808	Australian 230V
2090-0091	80% Shut Off-Kit

Distributed By:



Bacharach is a registered trademark of Bacharach, Inc.
© January 2009, Bacharach, Inc., all rights reserved. All information is subject to verification.
2009 - REV. 0 Printed in U.S.A.

